


Rocky Flats Environmental Technology Site

RECONNAISANCE LEVEL CHARACTERIZATION REPORT (RLCR)/PRE-DEMOLITION SURVEY REPORT (PDSR)

Tent 3 Closure Project

REVISION 0

June 14, 2005



Change Control:

- Rev 1. Revised Exec Summary and Section 1, clarified PDS surfaces 6/15/05.
- Rev 1. Revised Section 4.3, revised RCRA closure discussion 6/16/05.
- Rev 1. Revised Exec Summary, Sections 1, 3 & 8, and Attachment E; added text about additional pad survey per CR DAP-035, dated 6/16/05 6/16/05.
- Rev 1. Revised Exec Summary, Sections 1 & 8, changed RFCA Facility Type from 2 to 1 6/16/05.
- Rev 1. Revised Section 5, added text the removal of pond sludge piping system -6/16/05.

ADMIN RECORD

CLASSIFICATION REVIEW NOT REQUIRED PER EXEMPTION NUMBER CEX-005-02

1/41

.

RECONNAISANCE LEVEL CHARACTERIZATION REPORT (RLCR)/PRE-DEMOLITION SURVEY REPORT (PDSR)


Tent 3 Closure Project

REVISION 0

June 14, 2005

for Dan Risoli Date: 6/15/05 Reviewed by: Don Risoli, Quality Assurance Date: 6/15/05 Reviewed by: D.P. Snyder, RISS ESH&Q Manager Approved by:

Cameron Freiboth, K-H Project Manager



ABI	BRE	VIATIONS/ACRONYMS	III
EXI	E C U'	TIVE SUMMARY	IV
1		INTRODUCTION	
•	_		
-	.1	PURPOSESCOPE	
_	.2 .3	DATA QUALITY OBJECTIVES	
1	د.	•	
2		HISTORICAL SITE ASSESSMENT	2
3		RADIOLOGICAL CHARACTERIZATION AND HAZARDS	2
4		CHEMICAL CHARACTERIZATION AND HAZARDS	3
4	.1	ASBESTOS	
	.2	BERYLLIUM	
4	.3	RCRA/CERCLA CONSTITUENTS [INCLUDING METALS, VOLATILE ORGANIC COMPOUNDS	
		(VOCS) AND SEMI VOLATILE ORGANIC COMPOUNDS (SVOCS)]	4
4	.4	POLYCHLORINATED BIPHENYLS (PCBs)	4
5		PHYSICAL HAZARDS	5
6		DATA QUALITY ASSESSMENT	5
7		DECOMMISSIONING WASTE TYPES AND VOLUME ESTIMATES	5
8		FACILITY CLASSIFICATION AND CONCLUSIONS	6
9		REFERENCES	7
A TE	Tr A 4	CHIRADAUTC	
		CHMENTS Equility I continue Man	
A B		Facility Location Map Historical Site Assessment Report	
<u>-</u>		Radiological Data Summaries and Survey Maps	
Ď		Chemical Data Summaries and Sample Maps	
E		Data Quality Assessment (DQA) Detail	

ABBREVIATIONS/ACRONYMS

ACM Asbestos Containing Material

Be Beryllium

CDPHE Colorado Department of Public Health and the Environment

DCGL_{EMC} Derived Concentration Guideline Level – elevated measurement comparison

DCGLw Derived Concentration Guideline Level – Wilcoxon Rank Sum Test

D&D Decontamination and Decommissioning

DDCP Decontamination and Decommissioning Characterization Protocol

DOE U.S. Department of Energy
DPP Decommissioning Program Plan

DQA Data quality assessment DQOs Data quality objectives

EPA U.S. Environmental Protection Agency
FDPM Facility Disposition Program Manual
HVAC Heating, ventilation, air conditioning
HSAR Historical Site Assessment Report
HEUN Highly Enriched Uranyl Nitrate
IHSS Individual Hazardous Substance Site
IWCP Integrated Work Control Package

K-H Kaiser-Hill

LBP Lead-based paint LLW Low-level waste

MARSSIM Multi-Agency Radiation Survey and Site Investigation Manual

MDA Minimum detectable activity
MDC Minimum detectable concentration
NORM Naturally occurring radioactive material

NRA Non-Rad-Added Verification

OSHA Occupational Safety and Health Administration

PARCC Precision, accuracy, representativeness, comparability and completeness

PCBs Polychlorinated Biphenyls
PDS Pre-demolition survey
QC Quality Control

RCRA Resource Conservation and Recovery Act

RFCA Rocky Flats Cleanup Agreement

RFETS Rocky Flats Environmental Technology Site

RFFO Rocky Flats Field Office

RLC Reconnaissance Level Characterization

RLCR Reconnaissance Level Characterization Report

RSA Removable Surface Activity
RSP Radiological Safety Practices
SVOCs Semi-volatile organic compounds

TCLP Toxicity Characteristic Leaching Procedure

TSA Total surface activity

VOCs Volatile organic compounds

and in compliance with RFCA.

EXECUTIVE SUMMARY

A Reconnaissance Level Characterization (RLC) and a Pre-Demolition Survey (PDS) was performed to enable compliant disposition and waste management of Tent 3. Because this Type 1 structure will be demolished, the characterization was performed in accordance with the Pre-Demolition Survey Plan (MAN-127-PDSP). Structure surfaces characterized as part of this PDS included the tent fabric and metal structure supports comprising the walls, ceiling, and roof. The asphalt pad beneath the tent was radiologically surveyed in accordance with the Waste Release Evaluation (WRE) process, and all results were less than the unrestricted release criteria and are included in this PDSR. Additional RSP 7.02 surveys of the asphalt pad areas outside the Tent structures will be performed, after tent demolition is complete, for waste disposal determinations (refer to RFCA Contact Record (DAP-035), dated 6/20/05). Environmental media beneath and surrounding the structure was not within the scope of

The PDS encompassed both radiological and chemical characterization to enable compliant disposition and waste management pursuant to the D&D Characterization Protocol (MAN-077-DDCP). The characterization built upon physical, chemical and radiological hazards identified in the facility-specific *Historical Site Assessment Report for the Area 5 - Group 13 Facilities*, dated December 2002, Revision 0.

this PDS and will be addressed in accordance with the Soil Disturbance Permit process

Results indicate that no radiological, beryllium, asbestos or PCB contamination exists in excess of the PDSP unrestricted release limits. Sampling and analysis for RCRA/CERCLA constituents have been conducted as part of the RCRA closure process. The results of this sampling effort demonstrated that the tent structure is not a regulated hazardous waste, and is suitable for disposal at a sanitary landfill. However, the asphalt pad has not undergone RCRA closure and will be managed as hazardous waste (top layer) and sanitary waste (remaining layer).

Based on the analysis of radiological, chemical and physical hazards, Tent 3 is classified as RFCA Type 1 structure pursuant to the RFETS Decommissioning Program Plan (DPP; K-H, 1999) due the hazardous waste asphalt pad underneath the tent. Tent 3 can be demolished and the waste managed as sanitary waste. The asphalt pad will undergo RCRA closure by means of physical extraction. The layer removed will be managed as hazardous waste and the remainder of the pad will be managed as sanitary waste. To ensure the facility remains free of contamination and PDS data remain valid, Level 2 Isolation Controls have been established with the required postings.

Revi.

Ganj.



1 INTRODUCTION

A Reconnaissance Level Characterization (RLC) and a Pre-Demolition Survey (PDS) was performed to enable compliant disposition and waste management of Tent 3. Because this Type 1 structure will be demolished, the characterization was performed in accordance with the Pre-Demolition Survey Plan (MAN-127-PDSP). Building surfaces characterized as a part of this PDS included the walls, ceiling and roof. The asphalt pad beneath the tent was radiologically surveyed in accordance with the Waste Release Evaluation (WRE) process, and all results were less than the unrestricted release criteria and are included in this PDSR. Additional RSP 7.02 surveys of the asphalt pad areas outside the Tent structures will be performed, after tent demolition is complete, for waste disposal determinations (refer to RFCA Contact Record (DAP-035), dated 6/20/05). Environmental media beneath and surrounding the facility was not within the scope of this PDS and will be addressed in accordance with the Soil Disturbance Permit process and in compliance with RFCA.

Tent 3 was an "anticipated" Type 2 RFCA facility prior to the performance of this RLC/PDS effort. A Type 2 RLC had not yet been performed in this building because the tent had been in operation until recently, thus the majority of the tent surfaces were inaccessible for characterization. Since the performance of this RLC/PDS effort was performed in accordance with the Pre-Demolition Survey Plan (MAN-127-PDSP), no further characterization of this structure is necessary.

As part of the Rocky Flats Environmental Technology Site (RFETS) Closure Project, numerous facilities will be removed. Among these is Tent 3. The location of this structure is shown in Attachment A, *Facility Location Map*. This structure no longer supports the RFETS mission and will be removed to reduce Site infrastructure, risks and/or operating costs.

Before this Type 2 structure can be demolished, the Data Quality Objectives (DQOs) for a Pre-Demolition Survey (PDS) must be satisfied; this document presents the PDS results for Tent 3. The PDS was conducted pursuant to the Decontamination and Decommissioning Characterization Protocol (MAN-077-DDCP) and the Pre-Demolition Survey Plan for D&D Facilities (MAN-127-PDSP). The PDS was built upon physical, chemical and radiological hazards identified in the facility-specific *Historical Site Assessment Report for the Area 5 - Group 13 Facilities*, dated December 2002, Revision 0.

1.1 Purpose

The purpose of this report is to communicate and document the results of the Tent 3 PDS effort. A PDS is performed prior to building demolition to define the final radiological and chemical conditions of a facility. Final conditions are compared with the release limits for radiological and non-radiological contaminants. PDS results will enable project personnel to make final disposition decisions, develop related worker health and safety controls, and estimate waste volumes by waste types.







1.2 Scope

This report presents the final radiological and chemical conditions of the Tent 3 structure. Environmental media beneath and surrounding the structure are not within the scope of this PDSR and will be addressed in accordance with the Soil Disturbance Permit process and in compliance with RFCA.

1.3 Data Quality Objectives

The Data Quality Objectives (DQOs) used in designing this PDS were the same DQOs identified in the Pre-Demolition Survey Plan for D&D Facilities (MAN-127-PDSP). Refer to section 2.0 of MAN-127-PDSP for these DQOs. The radiological survey Data Quality Objectives (DQOs) for the asphalt pad satisfied per Radiological Safety Practice procedures 3-PRO-165-07.02, Contamination Monitoring Requirements.

2 HISTORICAL SITE ASSESSMENT

A facility-specific Historical Site Assessment Report (HSAR) was conducted to understand the facility history and related hazards. The assessment consisted of facility walk-downs, interviews, and document review, including review of the Historical Release Report (refer to the D&D Characterization Protocol, MAN-077-DDCP). Results were used to identify data gaps and needs, and to develop radiological and chemical characterization packages. Results of the facility specific HSA were documented in a facility specific Historical Site Assessment Report for the Area 5 - Group 13 Facilities, dated December 2002, Revision 0. Refer to Attachment B, Historical Site Assessment Report, for a copy of the Tent 3 HSAR. In summary, the HSAR identified a low potential for radiological, chemical, beryllium or asbestos hazards.

3 RADIOLOGICAL CHARACTERIZATION AND HAZARDS

Tent 3 was characterized for radiological hazards per the PDSP. Radiological characterization was performed to define the nature and extent of radioactive materials that may be present on the structure surfaces. Measurements were performed to evaluate the contaminants of concern. Based upon a review of historical and process knowledge, structure walk-downs, and MARSSIM guidance, a Radiological Characterization Plan was developed during the planning phase that describes the minimum survey requirements [refer to the RISS Characterization Project files for the Tent 3 Radiological Characterization Plan]. One Class 3 radiological survey unit package was developed for Tent 3: 750T03 (interior and exterior). A Class 3 designation was chosen since this survey unit has a low potential for contamination. Individual radiological survey unit packages are maintained in the RISS Characterization Project files.

RLCR/PDSR, Tent 3 Rocky Flats Environmental Technology Site Revision 0, 6/14/05 Page 3 of 7

The Tent 3 survey unit package was developed in accordance with Radiological Safety Practices (RSP) 16.01, Radiological Survey/Sampling Package Design, Preparation, Control, Implementation and Closure. Total surface activity (TSA), removable surface activity (RSA), and scan measurements were collected in accordance with RSP 16.02 Radiological Surveys of Surfaces and Structures. Radiological survey data were verified, validated and evaluated in accordance with RSP 16.04, Radiological Survey/Sample Data Analysis. Quality control measures were implemented relative to the survey process in accordance with RSP 16.05, Radiological Survey/Sample Quality Control.

A total of 31 total surface activity (TSA) measurements (17 random, 12 biased and 2 QC) and 29 removable surface activity (RSA) measurements (17 random and 12 biased) were taken and scan surveys performed. A minimum alpha scan survey of 15% of all interior and exterior surfaces at biased locations was performed. None of the measurements or scans indicated elevated activity above applicable DCGL values. The asphalt pad beneath Tent 3 will be released as part of the WRE and RCRA closure process. The Radiological Safety Practices (RSP) 7.02 procedure surveys of the asphalt pad that are included in Attachment C are of adequate quality and quantity to safely demolish the tent structure. These RSP 7.02 surveys of the asphalt pad were performed at evenly distributed locations and met TSA and RSA MDA PDSP requirements. Biased scans of stained areas (stained areas encompassed same locations as TSA/RSA locations) and areas along the tent edges were also performed. Additional RSP 7.02 surveys of the asphalt pad areas outside the Tent structures will be performed, after tent demolition is complete, for waste disposal determinations (refer to RFCA Contact Record (DAP-035), dated 6/20/05).

Radiological survey data, statistical analysis results, survey locations, asphalt pad WRE surveys, and radiological scan maps are presented in Attachment C, Radiological Data Summary and Survey Maps. Level 2 Isolation Control postings are displayed on the tent entrances to ensure no radioactive materials are introduced.

4 CHEMICAL CHARACTERIZATION AND HAZARDS

Tent 3 was characterized for chemical hazards per the PDSP. Chemical characterization was performed to determine the nature and extent of chemical contamination that may be present on, or in the structures. Based upon a review of historical and process knowledge, visual inspections, and PDSP DOOs, additional sampling needs were determined. A Chemical Characterization Plan was developed during the planning phase that describes sampling requirements and the justification for the sample locations and estimated sample numbers. The contaminants of concern were asbestos, beryllium, RCRA/CERCLA, lead and PCBs. Refer to Attachment D, Chemical Summary Data and Sample Maps, for details on sample results and sample locations. Isolation control postings are displayed on affected structures to ensure no hazardous materials are introduced.



4.1 Asbestos

A survey of building materials suspected of containing asbestos was conducted in Tent 3 as part of PDS activities. A CDPHE-certified asbestos inspector conducted the inspection in accordance with the Asbestos Characterization Protocol, PRO-563-ACPR, Revision 1. Building materials suspected of containing asbestos were identified for sampling at the discretion of the inspector. No materials suspected of containing asbestos were identified therefore, asbestos sampling was not performed as part of this RLC/PDS.

4.2 Beryllium

Based on the HSAR, Interview Checklists, and the Known Beryllium Area list, there was not adequate historical or process knowledge to conclude that beryllium was not present in Tent 3. Consequently, random and biased beryllium sampling was conducted in Tent 3 in accordance with PRO-536-BCPR, Beryllium Characterization Procedure. Biased beryllium sample locations corresponded with the most probable areas of dust accumulation (including beryllium dust), assuming airborne deposition. Random sample locations were computer generated.

All PDS beryllium laboratory results from Tent 3 were less than the investigative limit of 0.1 µg/100cm². PDS beryllium laboratory sample data and location maps are contained in Attachment D, Chemical Data Summaries and Sample Maps.

4.3 RCRA/CERCLA Constituents [including Metals, Volatile Organic Compounds (VOCs) and Semi Volatile Organic Compounds (SVOCs)]

Kenj.

A Closure Description Document (CDD) was submitted for RCRA Unit 750.1 including Tent 3 (05-RF-00218) and approved by CDPHE on March 23, 2005. The tent structure will be closed as denoted in the CDD. Since the asphalt pad is the RCRA secondary containment for the 750 Pad, and the pad has not yet undergone RCRA closure, the pad will undergo closure once the tent structure has been demolished. Tent 3 may have contained some RCRA regulated items, such as mercury thermostats, fluorescent light bulbs, mercury vapor light bulbs, mercury containing gauges, circuit boards, and lead-acid batteries. However, these items have been removed and are being managed in accordance with the Colorado Hazardous Waste Act. The Tent 3 structure will be removed and managed as sanitary waste. The asphalt pad will undergo proper RCRA closure by means of physical extraction. The layer removed will be managed as hazardous waste and the remainder of the pad will be managed as sanitary waste. All RCRA closure actions will be reported in the Closure Summary Report for the RCRA Unit 750.1.

Roub

4.4 Polychlorinated Biphenyls (PCBs)

Based on the HSAR for Tent 3, interviews, facility walk-downs and a review of historical WSRIC processes, the facility did not have a history of PCB use or storage. The structure may have contained PCB fluorescent light ballast, however, all PCB ballast have been removed from the structure. Consequently, PCB sampling and analysis was not conducted as part of this RLC/PDS and will not impact decontamination and decommissioning activities.

5 PHYSICAL HAZARDS

Physical hazards associated with Tent 3 consist of those common to standard industrial environments, and include hazards associated with energized systems, utilities, and trips and falls. There are no other unique hazards associated with the facility. The facility has been relatively well maintained and is in good physical condition, therefore, does not present any hazards associated with building deterioration. However, care should be taken as Tent 3 is located near the following IHSSs, PACs or UBCs:

- PAC 700-214, 750 Pad Pondcrete and Saltcrete Storage, Unit 25, Active
- IHSS 192, Seep Area Near OU-2 Influent, NFA 1999

Physical hazards are controlled by the Site Occupational Safety and Industrial Hygiene Program, which is based on OSHA regulations, DOE orders, and standard industry practices. The piping system that was installed in Tent 3 to move pond sludge from the sludge tanks to the Barn Tent mixing units was removed from the tent prior to the start of this RLC/PDS.



6 DATA QUALITY ASSESSMENT

Data used in making management decisions for decommissioning of Tent 3, and consequent waste management, are of adequate quality to support the decisions documented in this report. The data presented in this report (Attachments C and D) were verified and validated relative to DOE quality requirements, applicable EPA guidance, and original project DQOs.

In summary, the Verification and Validation (V&V) process corroborates that the following elements of the characterization process are adequate:

- the *number* of samples and surveys;
- the *types* of samples and surveys;
- the sampling/survey process as implemented "in the field"; and
- the laboratory analytical process, relative to accuracy and precision considerations.

Details of the DQA are provided in Attachment E.

7 DECOMMISSIONING WASTE TYPES AND VOLUME ESTIMATES

The demolition and disposal of Tent 3 will generate sanitary and hazardous waste. The tent structure will be managed and disposed of sanitary waste and the asphalt pad will be managed as hazardous waste (top layer) and the remainder of the pad will be managed as sanitary waste (remaining layer). Estimated waste types and waste volumes are presented below. PCB ballast and hazardous waste items have been removed and managed pursuant to Site PCB and waste management procedures.

	WASTE TYPES AND VOLUME ESTIMATES												
Facility	Concrete (cu ft)	Wood (cu ft)	Metal (cu ft)	Corrugated Sheet Metal (cu ft)	Wall Board (cu ft)	ACM (cu ft)	Other Waste (cu ft)						
Tent 3	0	0	2,500	0	0	0	Tent panels & misc. debris – 1,000						
Asphalt Pad	0	0	0	. 0	0	0	Hazardous waste- 5,000						

8 FACILITY CLASSIFICATION AND CONCLUSIONS

bon.

Based on the analysis of radiological, chemical and physical hazards, Tent 3 is classified as a RFCA Type 1 structure pursuant to the RFETS Decommissioning Program Plan (DPP; K-H, 1999). Tent 3 does not possess any radiological, asbestos or beryllium contamination in excess of the PDSP unrestricted release criteria. PCB ballast and hazardous waste items have been removed and disposed of in compliance with Environmental Protection Agency (EPA) and Colorado Department of Public Health and Environment (CDPHE) regulations.

boy.

The RLC/PDS for Tent 3 was performed in accordance with the DDCP and PDSP. All PDSP DQOs were met, and all data satisfied the PDSP DQA criteria. The asphalt pad beneath the tent was radiologically surveyed in accordance with the Waste Release Evaluation (WRE) process and meets the unrestricted release criteria. Additional RSP 7.02 surveys of the asphalt pad areas outside the Tent structures will be performed, after tent demolition is complete, for waste disposal determinations (refer to RFCA Contact Record (DAP-035), dated 6/20/05). Tent 3 can be demolished and the waste managed as sanitary waste. The asphalt pad will undergo RCRA closure by means of physical extraction. The layer removed will be managed as hazardous waste and the remainder of the pad will be managed as sanitary waste. Environmental media beneath and surrounding the facility will be addressed at a future date in accordance with the Soil Disturbance Permit process and in compliance with RFCA. To ensure Tent 3 remains free of contamination, Level 2 Isolation Controls have been established with the required postings.

9 REFERENCES

DOE/RFFO, CDPHE, EPA, 1996. Rocky Flats Cleanup Agreement (RFCA), July 19, 1996.

DOE Order 5400.5, "Radiation Protection of the Public and the Environment."

DOE Order 414.1A, "Quality Assurance."

EPA, 1994. "The Data Quality Objective Process," EPA QA/G-4.

K-H, 1999. Decommissioning Program Plan, June 21, 1999.

MAN-131-QAPM, Kaiser-Hill Team Quality Assurance Program, Rev. 1, November 1, 2001.

MAN-076-FDPM, Facility Disposition Program Manual, Rev. 3, January 1, 2002.

MAN-077-DDCP, Decontamination and Decommissioning Characterization Protocol, Rev. 4, July 15, 2002.

MAN-127-PDSP, Pre-Demolition Survey Plan for D&D Facilities, Rev. 1, July 15, 2002.

MARSSIM - Multi-Agency Radiation Survey and Site Investigation Manual, dated August 2000, Revision 1 (NUREG-1575, EPA 402-R-97-016).

PRO-475-RSP-16.01, Radiological Survey/Sampling Package Design, Preparation, Control, Implementation, and Closure, Rev. 1, May 22, 2001.

PRO-476-RSP-16.02, Pre-Demolition (Final Status) Radiological Surveys of Surfaces and Structures, Rev. 1, May 22, 2001.

PRO-477-RSP-16.03, Radiological Samples of Building Media, Rev. 1, May 22, 2001.

PRO-478-RSP-16.04, Radiological Survey/Sample Data Analysis for Final Status Survey, Rev. 1, May 22, 2001.

PRO-479-RSP-16.05, Radiological Survey/Sample Quality Control for Final Status Survey, Rev. 1, May 22, 2001.

PRO-563-ACPR, Asbestos Characterization Procedure, Revision 0, August 24, 1999.

PRO-536-BCPR, Beryllium Characterization Procedure, Revision 0, August 24, 1999.

RFETS, Environmental Waste Compliance Guidance #25, Management of Polychlorinated Biphenyls (PCBs) in Paint and Other Bulk Product Waste During Facility Disposition.


RFETS, Environmental Waste Compliance Guidance #27, Lead-Based Paint (LBP) and Lead-Based Paint Debris Disposal.

RFETS, RFCA RSOP for Recycling Concrete, September 28, 1999

RFETS, Historical Site Assessment Report for Area 5-Group 13, dated December 2002.

ATTACHMENT A

Facility Location Map



ATTACHMENT B

Historical Site Assessment Report

D&D RISS Facility Characterization Historical Site Assessment Report December, 2002 Rev. 0

Facility ID: (AREA 5 GROUP 13) Buildings S750, 750 Pad, Tent 02, Tent 03, Tent 04, Tent 05, Tent 06, and Tent 12.

Anticipated Facility Type (1, 2, or 3): Buildings S750, 750 Pad, Tent 02, Tent 03, Tent 04, Tent 05, Tent 06, and Tent 12 are anticipated Type 2 facilities.

This facility-specific Historical Site Assessment (HSA) has been performed in accordance with: D&D Characterization Protocol, RFETS MAN+077-DDCP, latest version, and Facility Disposition Program Manual, RFETS MAN-076-FDPM, latest version

Physical Description

Building S750

Building S750 is a 48 square-foot skid mounted portable shed acquired in the late 1980s or early 1990s. The shed has aluminum siding and an aluminum roof, the floor is wood.

Building S750 has the following utilities: electric.

The 750 Pad and associated tents (Tents 02, 03, 04, 05, 06, and 12)

The 750 Pad is approximately 100, 000 square-foot, fenced and bermed, asphalt pad that was built in 1987. The 750 Pad is estimated to be 4-inches thick and is sloped to control runoff. In 1990 six large tents (Tents 02, 03, 04, 05, 06, and 12) were added to the pad to enclose the Pondcrete and saltcrete waste management activities. In 2002 tent T-750 SPR was constructed to house the sludge stabilization equipment. The tents were constructed with fabric panel stretched across an aluminum frame and used steel anchored pins to mount the tents to the pad. The pad has installed piping for transferring the pond sludge from the storage tents to T750SPR for stabilization activities.

The 750 pad has the following utilities: electric and fire protection is provided by randomly placed fire extinguishers.

Tent 2, 3, 4, 5, 6, and 12

Tents 2, 3, 4, 5, 6, and 12 were constructed in approximately 1990 as a temporary storage facility for the storage and solidification of Pondcrete and Saltcrete. Tent T-750 SPR was constructed in 2002 to house pond sludge stabilization equipment. These tents are constructed with arched aluminum frames covered with polyester fabric. Tent 2 and 12 have a second layer of fabric to increase durability. The arched frames are anchored to the asphalt pad. Each tent has a containment berm around perimeter of the interior of each tent. Tent 5 houses a Perma-Con unit and a drum crusher.

Each tent is equipped with one or more vehicle access ways, metal access doors and 12-in-diameter wind turbine style ventilators. Tent 5 has a Perma-Con used to sample and repackage waste containers. The dimension of each tent is as follows; Tent 2 - 50 ft. wide by 180 ft. long by 24 ft. high; Tent 3 - 60 ft. wide by 176 ft. long by 24 ft. high; Tent 4 - 60 ft. wide by 180 ft. long by 24 ft. high; Tent 5 - 60 ft. wide by 180 ft. long by 24 ft. high; Tent 6 - 60 ft. wide by 360 ft. long by 24 ft. high; Tent 12 - 60 ft. wide by 280 ft. long by 24 ft. high; and Tent T-750 - 60 ft. wide by 80 ft. long by 24 feet high.

Each Tent has the following utilities: electric and fire protection is provided by randomly placed fire extinguishers.

D&D RISS Facility Characterization Historical Site Assessment Report December, 2002 Rev. 0

Historical Operations

Building S750

Building S750 is a shed that was installed in the late 1990s. This shed has primarily been used as a storage shed for non-hazardous and non-radiological operation such as the site housekeeping services, food service organization and site maintenance organization. There is no history of any radiological or Hazardous operations.

The 750 pad and Tents 2, 3, 4, 5, 6, 12, and T-750 SPR

The 750 pad is a large asphalt-paved area located east of Building 750. The 750 Pad and the associated tents (Tents 2, 3, 4, 5, 6, 12, and T-750 SPR) are used to store LLW, LLW-Mixed, and hazardous waste. Tents 2 and 12 can be used to store TRU and TRU-Mixed waste. Waste is stored in Tri-wall boxes, plywood crates, corrugated boxes, metal crates, and pond sludge storage tanks. Tent 5 has a Perma-Con used to repackage and samples waste, and a drum crusher. Tent T-750 SPR was constructed in 2002 and house the pond sludge stabilization equipment. A piping system has been installed to move the pond sludge from the tents 3, 4, and 5 to Tent T-750SPR for stabilization. The 750 Pad and the associated tents primarily store Pondcrete, Saltcrete, pond sludge, investigative derived waste and to a lesser extent process generated waste from various operation inside the Protected area. See the 750 Pad WSRIC and Safety Analysis Report for additional information. There have been several small releases to the 750 Pad. Additional release information can be found in IHH, PAC, and UBC section below.

Tent 5 holds the Perma-Con unit used to repackage and sample waste containers and the drum-crushing unit. A second Perma-con is being built in Tent 5 to assist in the waste repackaging and sampling activities. Tent 3, 4, and 6 are primarily used to house Pondcrete storage tanks and Tents 2, 6, and 12 are primarily used to store waste drums and crates.

The 750 pad and associated tents hours the following RCRA units:

- 1) RCRA Unit 750-1, which addresses container storage, and will be closed in accordance with RCRA Part B Permit No. CO 97-05-30-01.
- 2) RCRA Unit 750.2, which addresses the Pondcrete storage, tanks, and will be closed in accordance with RCRA Part B Permit No. CO-97-05-30-01.
- 3) RCRA Unit 750.3 that addresses sludge de-watering and stabilization processes. The sludge de-watering equipment has been removed and RCRA Closure is in progress. The stabilization process is still active. Closure will be performed in accordance with RCRA Part B Permit No. CO-97-05-30-01.

Current Operational Status

Buildings S750, the 750 Pad and the associated tents are all operational.

Contaminants of Concern

—— D&D RISS Facility Characterization Historical Site Assessment Report December, 2002 Rev. 0

Asbestos

Describe any potential, likely, or known sources of Asbestos:

None of the facilities addressed in this HSA have an asbestos posting.

Bervllium (Be)

Describe any potential, likely, or known Be production or storage locations:

The 750 pad and Tents 2, 3, 4, 5, 6, 12 and the Perma-Con in Tent 5 are all on the RFETS list of Historic and Present Beryllium Areas. Tent T-750-SPR was constructed in 2002 and has no current Data.

Summarize any recent Be sampling results:

See Industrial Hygiene group has a list of the most recent Be samples collected for the facilities addressed in this HSA.

Lead

Describe any potential, likely, or known sources of Lead (e.g., paint, shielding, etc.):

Based on the age of some of the facilities addressed in this HSA, lead in paint should not be a concern. No processes containing lead were conducted in these facilities.

RCRA/CERCLA Constituents

Describe any potential, likely, or known sources of RCRA/CERCLA constituents (e.g., chemical storage, waste storage, and processes):

Building S750 has no history of Hazardous operations. The 750 Pad and the Associated tents where used to Store LLW, LLW-Mixed, TRU, TRU-Mixed, and hazardous waste streams. See the Historical Operation section above for a more detailer description of the activities which occurred on the 750 Pad. See the 750 Pad WSRIC for a more detailer description of the waste streams handled on the 750 Pad. See the IHSS, PAC, and UBC section below for release information.

Describe any potential, likely, or known spill locations (and sources, if any):

The 750 Pad and the associated tents have had several small releases, some of these releases are documented in PAC 700-214, "750 Pad Pondcrete and Saltcrete Storage, Unit 25".

Describe methods in which spills were mitigated, if any:

Spills were cleaned by sweeping, washing, wiping or scooping.



D&D RISS Facility Characterization Historical Site Assessment Report December, 2002 Rev. 0

PCBs

Describe any potential, likely, or known sources of PCBs (e.g., light ballasts, paints, equipment, etc.):

No PCB containing process where housed in any of the facilities addressed in this HSA. No process equipment containing PCBs were located in any of these facilities. The 750 Pad (and the associated tents) were never used a permitted TSCA waste storage area. Based on the age of construction of some of these facilities, PCBs in paint should not be a concern.

Describe any potential, likely, or known spill locations (and sources, if any):

No PCB spills occurred in any of the Facilities addressed in this HSA.

Describe methods in which spills were mitigated, if any:

No PCB spills occurred in any of the Facilities addressed in this HSA.

Radiological Contaminants

Describe any potential, likely, or known radiological production or storage locations:

The 750 Pad (including Tents 2, 3, 4, 5, 6, and 12), have radiological postings, The 750 Pad, and the associated Tents are permitted LLW, LLWN TRU and TRUM waste storage units. Waste stored on the 750 Pad is primarily Pondcrete, and Saltcrete. See the 750 Pad WSRIC for more information on the waste stored on the 750 Pad. See the Historical Operations section above for a more detailed listing of the operations which occurred in the facilities addressed in this HSA.

Describe any potential, likely, or known spill locations (e.g., known leaking sealed radioactive sources, leaking waste drums, potentially contaminated drains, etc.):

The 750 Pad and the associated tents have had several small releases, some of which are documented in the IHSS, PAC, and UBC section below.

Describe methods in which spills were mitigated, f any:

Spills were cleaned by sweeping, washing, wiping or scooping.

Describe any potential, likely, or known isotopes of concern (e.g., weapons grade plutonium, uranium isotopes, pure beta emitters, mixed fission products, etc.):

Isotopes of concern include uranium and plutonium.

Describe any potential, likely, or known external facility contamination (e.g., stack release points, unfiltered ventilation, facility's physical location to known site releases, etc.):

See section below for information on IHSSs PACs, and UBCs.

D&D RISS Facility Characterization Historical Site Assessment Report December, 2002 Rev. 0

Environmental Restoration Concerns

Describe any ER concerns that could affect facility characterization (e.g., IHSSs, PACs, UBCs):

The 750 Pad and Tents 2, 3, 4, 5, 6, 12, and T-750 SPR are located on the following IHSSs, PACs, or UBCs. See individual IHSS, PAC, or UBC report for additional information.

- 1) PAC 700-214, "750 Pad Pondcrete and Saltcrete Storage, Unit 25", Active.
- 2) IHSS 192 "Seep Area Near OU-2 Influent", NFA, 1999.

Building \$750 is not associated with any IHSSs, PACs, or UBCs.

Additional Information

Describe any additional information that may be useful during facility characterization (e.g., contaminant migration routes, waste handling operations, physical hazards, Historical Release Reports, WSRIC data, etc.):

None

References

Provide all sources of information utilized to gather data for facility history (e.g., documents, files, interviews):

Sources reviewed to complete this HSA were the RFETS Facility List, the Historical Release Report, Site Master List of RCRA Units, and the Site IHSS, PAC, and UBC databases. The WSRIC for those buildings with a WSRIC. In addition, a facility walkdown and interviews were performed.

Waste Volume Estimates and Material Types

Waste Volume Estimates and Waterian Lypes												
Facility	Concrete (cu ft)	Wood (cu ft)	Metal (cu ft)	Corrugated Sheet Metal (cu ft)	Wall Board (cu ft)	ACM (cu ft)	Other Waste (cu ft)					
S750	0	50	50	50	0	TBD	N/A					
750 Pad	. 0	0	0	0	0	TBD	Asphalt 50,000					
Tent 2	0	0	2300	0	0	TBD	Fabric- 1000					
Tent 3	0	0	2300	0	0	TBD	Fabric- 1200					
Tent 4	0	0	2500	0	0	TBD	Fabric- 1300					
Tent 5	0	0	2500	0	0	TBD	Fabric- 1300					
Tent 6	0	0	5000	0	0	TBD	Fabric- 2600					
Tent 12	0	0	3100	0	0	TBD	Fabric- 1900					

Further Actions

Recommend any further actions, if any (e.g., characterization, decontamination, special handling, etc.):

Begin the RLC/PDS process.

B&D RISS Facility Characterization Historical Site Assessment Report December, 2002 Rev. 0

and the newer data will take precedence over the data in this report. Newer Data will appear in the RLCR/PDSR.
characterization package preparations, which may conflict with this report. However, this report will not be amended,
"snapshot" in time. Subsequent data may be obtained during SME walkdowns and chemical and radiological
review additional documentation and perform; additional interviews. Information contained in this HSA only represents a
preparations. SMEs should evaluate and/or verify all information during the RLC/PDS process. SMEs may need to
This HSA was performed prior to SME walkdowns, and chemical and radiological characterization package
Note:

•				
	Date	Signature	Name	•
	December 2002	1 Sm- 124	Doug Bryant	Prepared By:
	Line	the book not		

ATTACHMENT C

Radiological Data Summaries And Survey Maps

Survey Area: 5

Survey Unit: 750T03

Building: TENT 3

Description: Tent 3, Interior and Exterior, except asphalt pad

Rocky Flats Environmental Technology Site Final Radiological Survey Summary Results

Total Surface Activity Measurements

Nbr Random Measurements Required: 17

Nbr Biased Measurements Required: 10

Nbr QC Required: 2

Nbr Random Measurements Performed: 17

Nbr Biased Measurements Performed: 12

Nbr QC Performed: 2

Alpha

Maximum:

73.5 dpm/100cm²

Minimum:

-6.6 dpm/100cm²

Mean:

27.9 dpm/100cm²

Standard Deviation:

25.5

QC Maximum:

27.4 dpm/100cm²

QC Minimum:

5.1 dpm/100cm²

QC Mean:

16.2 dpm/100cm²

Transuranic DCGLw:

100.0 dpm/100cm²

Transuranic DCGLEMC:

300.0 dpm/100cm²

Removable Surface Activity Measurements

Nbr Random Measurements Required: 17

Nbr Biased Measurements Required: 10

Nbr Random Measurements Performed: 17

Nbr Biased Measurements Performed: 12

Alpha

Maximum:

4.5 dpm/100cm²

Minimum:

-1,2 dpm/100cm²

Mean:

1.3 dpm/100cm²

Standard Deviation:

1.6

Transuranic DCGLw:

20.0 dpm/100cm²

Media Sample Results

Nbr Random Required: 0

Nbr Biased Required: 0

Nbr Random Collected: 0

Nbr Biased Collected: 0

Conclusion - A comparison of the random, biased and QC measurement results against the PDSP Table 7-1 Surface Contamination Guideline limits was conducted; the comparison demonstrates that this survey unit passes the criterion specified in the PDSP.

Printed On: 06/14/05 14:38

of 7 Page: 1

Survey Area: 5

Survey Unit: 750T03

Building: TENT 3

Description: Tent 3, Interior and Exterior, except asphalt pad

Instrument Data Sheet

Inst/R	CT RCT	, , , , , , , , , , , , , , , , , , , ,	Instr	Instru	Probe	Calibration	Instru Efficiency		A-Priori MDA (dpm/100cm²)		Survey
Numb	er ID	Date	Model	S/N	Туре	Due Dt	Alpha	Beta	Alpha	Beta	Туре
1	510643	06/06/05	Electra	3127	DP-6	08/21/05	0.206	NA	300.0	NA	s
2	510643	06/07/05	Electra	3127	DP-6	08/21/05	0.206	NA	300.0	NA	s
3	507846	06/07/05	Electra	3102	DP-6	06/16/05	0.216	NA	300.0	NA	S
4	511466	06/08/05	Electra	3102	DP-6	06/16/05	0.216	NA	48.0	NA	T/S
5	510643	06/08/05	Electra	3127	DP-6	08/21/05	0.206	NA	48.0	NA	T/S
6	510643	06/09/05	Electra	3127	DP-6	08/21/05	0.206	NA	48.0	NA	T/Q/S
7	511466	06/09/05	SAC-4	767	NA	08/03/05	0.330	NA	10.0	NA	R
8	511466	06/09/05	SAC-4	1130	NA	07/03/05	0.330	NA	10.0	NA	R

Survey Types: T = Total Surface Activity, Q = TSA QC, S = Scan, R = Removable Surface Activity, I = Investigation

Printed On: 06/14/05 14:38

Page: 2 of 7

Survey Unit: 750T03 Building: TENT 3 Survey Area: 5

Description: Tent 3, Interior and Exterior, except asphalt pad

Comments Sheet

General N/A Comments:

TSA For instruments that were used for both TSAs and scans (T/S) on the Instrument Data Sheet, The TSA A-Priori MDA is 48.0 and the

Comments: scan A-Priori MDA is 300.0.

Ventilation sleeve drops in tent ceiling were included in the scan surveys of the tent. No elevated count rates above the DCGLw were

RSA N/A

Comments:

Media N/A

Comments:

Printed On: 06/14/05 14:38

of 7 Page: 3

Description: Tent 3, Interior and Exterior, except asphalt pad

Random Removable Surface Activity Data Sheet

Random Measurement Location	Inst / RCT Nbr	Net Alpha (dpm/100cm²)	Net Beta (dpm/100cm²)	
750T03PRP-N001	7	1.5	N/A	N/A
750T03PRP-N002	8	-1.2	N/A	N/A
750T03PRP-N003	7	0.0	N/A	N/A
750T03PRP-N004	8	0.3	N/A	N/A
750T03PRP-N005	7	4.5	N/A	N/A
750T03PRP-N006	8	0.3	. N/A	N/A
750T03PRP-N007	7	1.5	N/A	N/A
750T03PRP-N008	8	1.8	N/A	N/A
750T03PRP-N009	7	0.0	N/A	N/A
750T03PRP-N010	8	-1.2	N/A	N/A
750T03PRP-N011	7	1.5	N/A	N/A
750T03PRP-N012	8	0.3	N/A	N/A
750T03PRP-N013	7	3.0	N/A	N/A
750T03PRP-N014	8	1.8	N/A	N/A
750T03PRP-N015	7	1.5	N/A	N/A
750T03PRP-N016	8	1.8	N/A	N/A
750T03PRP-N017	7	4.5	N/A	N/A

Printed On: 06/14/05 14:38

Page: 4 of 7

Description: Tent 3, Interior and Exterior, except asphalt pad

Biased Removable Surface Activity Data Sheet

Biased Measurement Location	Inst / RCT Nbr	Net Alpha (dpm/100cm²)	Net Beta (dpm/100cm²)	
750T03PBP-N018	8	0.3	N/A	N/A
750T03PBP-N019	7	3.0	N/A	N/A
750T03PBP-N020	8	1.8	N/A	N/A
750T03PBP-N021	7	0.0	N/A	N/A
750T03PBP-N022	8	-1.2	N/A	N/A
750T03PBP-N023	7	1.5	N/A	N/A
750T03PBP-N024	8	0.3	N/A	N/A
750T03PBP-N025	7	3.0	N/A	N/A
750T03PBP-N026	8	0.3	N/A	N/A
750T03PBP-N027	7	4.5	N/A	N/A
750T03PBP-N028	8	1.8	N/A	N/A
750T03PBP-N029	7	1.5	N/A	N/A

Printed On: 06/14/05 14:38

Page: 5 of 7

Description: Tent 3, Interior and Exterior, except asphalt pad

Random/QC Total Surface Activity Data Sheet

Random Measurement Location	Inst / RCT Nbr	Net Alpha (dpm/100cm²)	Net Beta (dpm/100cm²)	
750T03PRP-N001	4	24.0	N/A	N/A
750T03PRP-N002	4	70.3	N/A	N/A
750T03PRP-N003	4	5.4	N/A	N/A
750T03PRP-N004	4	45.7	N/A	N/A
750T03PRP-N005	4	42.5	N/A	N/A
750T03QRP-N005	6	27.4	N/A	N/A
750T03PRP-N006	4	2.7	N/A	N/A
750T03PRP-N007	4 .	55.0	· N/A	N/A
750T03PRP-N008	4	-6.6	N/A	N/A
750T03PRP-N009	4	24.0	N/A	N/A
750T03PRP-N010	4	2.7	N/A	N/A
750T03PRP-N011	4	5.4	· N/A	N/A
750T03PRP-N012	4	49.0	N/A	N/A
750T03PRP-N013	4	24.0	N/A	N/A
750T03QRP-N013	6	5.1	N/A	N/A
750T03PRP-N014	4	2.7	N/A	N/A
750T03PRP-N015	4	61.0	N/A	N/A
750T03PRP-N016	4	36.5	N/A	N/A
750T03PRP-N017	4	73.5	N/A	N/A

28

Printed On: 06/14/05 14:38

Page: 6 of 7

Description: Tent 3, Interior and Exterior, except asphalt pad

Biased Total Surface Activity Data Sheet

Biased Measurement Location	Inst / RCT Nbr	Net Alpha (dpm/100cm²)	Net Beta (dpm/100cm²)	
750T03PBP-N018	4	1.7	N/A	N/A
750T03PBP-N019	5	2.7	N/A	N/A
750T03PBP-N020	4	-4.8	N/A	N/A
750T03PBP-N021	5	31.8	N/A	N/A
750T03PBP-N022	4	26.2	N/A	N/A
750T03PBP-N023	5	25.0	N/A	N/A
750T03PBP-N024	4	72.5	N/A	N/A
750T03PBP-N025	5	15.3	N/A	N/A
750T03PBP-N026	4	72.5	N/A	N/A
750T03PBP-N027	5	9.0	N/A	N/A
750T03PBP-N028	6	9.0	N/A	N/A
750T03PBP-N029	6	29.9	N/A	N/A

29

Printed On: 06/14/05 14:38

Page: 7 of 7

PRE-DEMOLITION SURVEY FOR TENT 3

Survey Area: 5 Survey Unit: 750T03 Classification: 3
Building: Tent 3
Survey Unit Decription: Tent 3 Interior & Exterior (excluding asphalt pad)
Total Area: 2,715 sq. m. Total Floor Area: 1,077 sq. r

Total Floor Area: 1,077 sq. m.

PAGE 1 OF 1

SURVEY MAP LEGEND

Smear & TSA Location

Smear, TSA & Sample Locatio Open/Inaccessible Area Area in Another Survey Unit

Neither the United States Government nor Kaiser Hill Co. nor CH2MHill, nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information,

Scan Survey Information Survey Instrument ID #(s) & RCT ID #(s):

FEET **METERS** 1 inch = 24 feet 1 grid sq. = 1 sq. m. U.S. Department of Energy Rocky Flats Environmental Technology Site


epared by: GIS Dept. 303-966-7707

CH2MHILL Communications Group MAP ID: 03-JS\A5G13\Tent03

Feb. 1, 2005

Scan Area

750 Pad ~ Tent 03 Exterior (Flattened)




	ROCKY FLATS ENVIRONMENTAL TECHNOLOGY SITE												
	1	NSTRUM	ENT DAT	Ά,	Survey Tracking # N/A								
Mfg.	Eberline	Mfg. N	IE Electra	Mfg. N	NE Electra	Survey Type: Contamination (fixed and removable)							
Model	SAC-4	Model	DP-6	Model :	DP-6	Building: Tent 3							
Serial #	767	Serial #	3102	Serial #	3127 ⁻	Location: 750 pad							
Cal Due	8/3/05	Cal Due	6/16/05	Cal Due `	8/21/05	Purpose: Survey of asphalt pad inside tent 3							
Bkg	0.1 cpmα	Bkg	6.0 cpmα	Bkg	4.0 cpmα	,							
Efficiency	33.00 %	Efficiency	21.60 %	Efficiency	20.60 %	RWP#: N/A							
MDA	20 dpmα	MDA	64 dpmα	MDA	57 dpmα								
I						Date: 6/8/05 Time: 1600							
Mfg.	N/A	Mfg.	N/A	Mfg.	N/A								
Model	N/A	Model	N/A	Model	N/A	RCT: S. Jablkowski M. pblkowski							
Serial #	N/A	Serial #	N/A	Serial #	N/A	Print name / Signature							
Cal Due	N/A	Cal Due	/A	Cal Due	N/A	10 10							
Bkg	N/A cpmβ	Bkg	N/A cpmβ	Bkg	N/A cpmβ	RCT: A. Vigil							
Efficiency	N/A %	Efficiency	N/A %	Efficiency	N/A %	Print name Signa ture							
MDA	N/A dpmβ	MDA	N/A dpmB	MDA	N/A dpmβ								
Comment	: Nuclide	of concern i	s plutonium	. Floor area	a around eac	h point was scanned in a 2 square meter area, and on the							
	areas near the edge of tent denoted on map with no contamination found above the MDA's of the instrument												
	listed ab		-1			A 1 = (A (A (A ())) =							
	Scan	5 of 3	stained a	areas u	vere also	performed around TSA/RSA locations.							

		<u> </u>	ALPHA			BETA												
	LOCATION	Swipe	Direct	Wipe	Swipe	Direct	Wipe											
#		dpm/100cm2	dpm/100cm2	dpm/wipe	dpm/100cm2	dpm/100cm2	dpm/wip											
1	On pad	` <20	<64	N/A	N/A	N/A	N/A											
2	On pad	<20	<64	N/A	N/A	N/A	N/A											
3	On pad	<20	<64	N/A	N/A	N/A	N/A											
4	On pad ,	<20	<64	N/A	N/A	N/A	N/A											
5 .	. On pad	<20	<64	N/A	N/A	N/A	N/A											
6	On pad	<20	<64	N/A	N/A	N/A	N/A											
7	On pad	<20	<64	N/A	N/A	N/A	N/A											
8	On pad	<20	<64	N/A	N/A	N/A	N/A											
9	On pad	<20	<64	N/A	N/A_	N/A	N/A											
10	On pad	<20	<64	N/A	N/A	N/A	N/A											
11	On pad	<20	<64	N/A	N/A	N/A	N/A											
12	On pad	<20	<64	N/A	N/A	N/A	N/A											
13	On pad	<20	<64	N/A	N/A	N/A	N/A											
14	On pad	<20	<64	N/A	N/A	N/A	N/A											
N/A	N/A	N/A	N/A	N/A	· N/A	N/A	N/A											
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A											
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A											
N/A	N/A	N/A	N/A	N/A	N/A_	N/A	N/A											
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A											
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A											
Date Reviewed:	6/10/05 RS Supervision:	G. S. Treadwel	11 /	80	ember	\mathcal{M}_1												

Print Name

SURVEY RESULTS




ATTACHMENT D

Chemical Data Summaries And Sample Maps

Beryllium Data Summary

Sample Number	Map Survey Point Location	Room	Sample Location	Result (ug/100 cm ²)		
	Tent 3 - RIN 05Z1229					
750-06062005-214-039 13 Main asphalt pad < 0.1						
750-06062005-214-040	21	Main	asphalt pad	< 0.1		
750-06062005-214-041	27	Main	asphalt pad	< 0.1		
750-06062005-214-042	3	Main	asphalt pad	< 0.1		
750-06062005-214-043	18	Main	asphalt pad	< 0.1		
750-06062005-214-044	9	Main	asphalt pad	< 0.1		
750-06062005-214-045	19	Main	asphalt pad	< 0.1		
750-06062005-214-046	17	Main	asphalt pad	< 0.1		
750-06062005-214-047	16	Main	asphalt pad	< 0.1		
750-06062005-214-048	20	Main	asphalt pad	< 0.1		
750-06062005-214-049	26	Main	asphalt pad	< 0.1		
750-06062005-214-050	5	Main	asphalt pad	< 0.1		
750-06062005-214-051	1	Main	asphalt pad	< 0.1		
750-06062005-214-052	8	Main	asphalt pad	< 0.1		
750-06062005-214-053	28	Main	asphalt pad	< 0.1		
750-06062005-214-054	24	Main	asphalt pad	< 0.1		
750-06062005-214-055	15	Main	asphalt pad	< 0.1		
750-06062005-214-056	23	Main	asphalt pad	< 0.1		
750-06062005-214-057	14	Main	asphalt pad	< 0.1		
750-06062005-214-058	2	Main	asphalt pad	< 0.1		
750-06062005-214-059	22	Main	asphalt pad	< 0.1		
750-06062005-214-060	11	Main	asphalt pad	< 0.1		
750-06062005-214-061	4	Main	asphalt pad	< 0.1		
750-06062005-214-062	12	Main	asphalt pad	< 0.1		
750-06062005-214-063	25	Main	asphalt pad	< 0.1		
750-06062005-214-064	10	Main	asphalt pad	< 0.1		
750-06062005-214-065	6	Main	asphalt pad	< 0.1		
750-06062005-214-066	7	Main	asphalt pad	< 0.1		
750-06062005-214-067	36	Main	Tent ceiling	< 0.1		
750-06062005-214-068	35	Main	Tent ceiling	< 0.1		
750-06062005-214-069	31	Main	Tent ceiling	< 0.1		
750-06062005-214-070	37	Main	Tent ceiling	< 0.1		
750-06062005-214-071	39	Main	Tent ceiling	< 0.1		
750-06062005-214-072	32	Main	Tent ceiling	< 0.1		
750-06062005-214-073	34	Main	Tent ceiling	< 0.1		
750-06062005-214-074	29	Main	Tent ceiling < 0.1			
750-06062005-214-075	30	Main	Tent ceiling < 0.			
750-06062005-214-076	33	Main	Tent ceiling	< 0.1		
750-06062005-214-077	38	Main	Tent ceiling	< 0.1		

Note 1: Sample numbers 750-06062005-214-067 through 750-06062005-214-077 were randomly generated but are considered bias samples as they have been moved from their floor location to the tent ceiling directly above their floor location.



ATTACHMENT E

Data Quality Assessment (DQA) Detail

DATA QUALITY ASSESSMENT (DQA)

VERIFICATION & VALIDATION (V&V) OF RESULTS

V&V of the data confirm that appropriate quality controls are implemented throughout the sampling and analysis process, and that any substandard controls result in qualification or rejection of the data in question. The required quality controls and their implementation are summarized in a tabular, checklist format for each category of data – radiological surveys and chemical analyses (specifically beryllium).

DQA criteria and results are provided in a tabular format for each suite of surveys or chemical analyses performed. The radiological survey assessment is provided in Table E-1 and beryllium in Table E-2. A data completeness summary for all results is given in Table E-3.

All relevant Quality records supporting this report are maintained in the RISS Characterization Project File. The report will be submitted to the CERCLA Administrative Record for permanent storage within 30 days of approval by the Regulators. All radiological data are organized into Survey Packages, which correlate to unique (MARSSIM) Survey Units. Chemical data are organized by RIN (Report Identification Number) and are traceable to the sample number and corresponding sample location.

Beta/gamma survey designs were not implemented for Tent 3 based on the conservatism of the transuranic limits used as DCGLs in the unrestricted release decision process. Survey designs were implemented based on the transuranic limits used as DCGLs in the unrestricted release decision process. Transuranic isotope activity and Uranium and/or other naturally occurring isotope activity were evaluated against, and were less than the Transuranic DCGL_w (100 dpm/100cm²) unrestricted release limits.

Consistent with EPA's G-4 DQO process, the radiological survey design for each survey unit performed per PDS requirements was optimized by checking actual measurement results acquired during pre-demolition surveys against the model output with original estimates. Use of actual sample/survey (result) variances in the MARSSIM DQO model confirms that an adequate number of surveys were acquired. The radiological survey Data Quality Objectives (DQOs) for the asphalt pad were satisfied per Radiological Safety Practice procedures 3-PRO-165-07.02, Contamination Monitoring Requirements. Additional RSP 7.02 surveys of the asphalt pad areas outside the Tent structures will be performed, after tent demolition is complete, for waste disposal determinations (refer to RFCA Contact Record (DAP-035), dated 6/20/05).



DQA SUMMARY

In summary, the data presented in this report have been verified and validated relative to the quality requirements and project decisions as stated in the original DQOs. All data are useable based on qualifications stated herein and are considered satisfactory without qualification. All media surveyed and sampled yielded results less than their associated action levels and with acceptable certainties.

Based upon an independent review of the radiological data, it is determined that the original project DQOs satisfied MARSSIM guidance. All facility contamination levels were below applicable DCGL unrestricted release levels. Minimum survey requirements were met, sampling/survey protocol was performed in accordance with applicable RSPs, survey units were properly designed and bounded, and instrument performance and calibration was verified as acceptable thereby ensuring data accuracy criteria. All results meet the PDS unrestricted release criteria.

Chain of Custody was intact; documentation was complete, hold times were acceptable (where applicable,) and packaging integrity/custody seals were maintained throughout the sampling/analysis process. Level 2 Isolation Controls have been posted to prevent the inadvertent introduction of contamination into the facilities. On this basis, Tent 3 meets the unrestricted release criteria with the confidences stated.



 $Table \ E\text{-}1 \ V\&V \ of \ Radiological \ Results - Tent \ 3$

V&V CRITERIA, RADIOLGICAL SURVEYS		K-H RSP 16.00 Series MARSSIM (NUREG-1575)		
	QUALITY REQUIREMENTS	r		
	Parameters	Measure	Frequency	COMMENTS
ACCURACY	Initial calibrations	90% <x<110%< td=""><td>≥1</td><td>Multi-point calibration through the measurement range encountered in the field; programmatic records.</td></x<110%<>	≥1	Multi-point calibration through the measurement range encountered in the field; programmatic records.
	Daily source checks	80% <x<120%< td=""><td>≥1/day</td><td>Performed daily/within range.</td></x<120%<>	≥1/day	Performed daily/within range.
	Local area background: Field	typically < 10 dpm	≥1/day	All local area backgrounds were within expected ranges (i.e., no elevated anomalies.)
PRECISION	Field duplicate measurements for TSA	≥5% of real survey points	≥10% of reals	N/A
REPRESENTATIVENESS	MARSSIM methodology: Survey Unit 750T03 (interior and exterior).	statistical and biased	NA	Random w/ statistical confidence.
	Survey Maps	NA	NA	Random and biased measurement locations controlled/mapped to ±1m.
	Controlling Documents (Characterization Pkg; RSPs)	qualitative	NA	Refer to the Characterization Package (planning document) for field/sampling procedures (located in Project files); thorough documentation of the planning, sampling/analysis process, and data reduction into formats.
COMPARABILITY	Units of measure	dpm/100cm ²	NA	Use of standardized engineering units in the reporting of measurement results.
COMPLETENESS	Plan vs. Actual surveys Usable results vs. unusable	>95% >95%	NA	See Table E-3 for details.
SENSITIVITY	Detection limits	TSA: ≤50 dpm/100cm ² RA: ≤10 dpm/100cm ²	all measures	MDAs ≤ 50% DCGL _w Note: The waste characterization surveys of the asphalt pad met the MDA requirements for waste packaging and disposal but not the PDSP requirements. However, since this material will not be unrestricted released, but rather disposed of as hazardous waste, the stated MDAs are adequate.

Table E-2 V&V of Beryllium Results - Tent 3 $\,$

V&V CRITERIA, CHEMICAL ANALYSES		DATA PACKAGE		
BERYLLIUM	Prep: NMAM 7300 METHOD: OSHA ID-125G	LAB>	Johns Manville Littleton, Co.	
		RIN>	RIN05Z1229	
			· · · · · · · · · · · · · · · · · · ·	COMMENTS
QUALITY	REQUIREMENTS	Measure	Frequency	All results were below associated action levels.
ACCURACY	Calibrations Initial	linear calibration	≥1	
	Continuing	80%<%R<120%	≥1	
	LCS/MS	80%<%R<120%	≥l	
	Blanks - lab & field	<mdl< td=""><td>≥1</td><td></td></mdl<>	≥1	
	Interference check std (ICP)	NA	NA	
PRECISION	LCSD	80%<%R<120% (RPD<20%)	≥l	
	Field duplicate	all results < RL	≥l	
REPRESENTATIVENESS	COC	Qualitative	NA	
	Hold times/preservation	Qualitative	NA	
	Controlling Documents (Plans, Procedures, maps, etc.)	Qualitative	NA	,
COMPARABILITY	Measurement units	ug/100cm ²	NA]
COMPLETENESS	Plan vs. Actual samples Usable results vs. unusable	>95% >95%	NA	
SENSITIVITY	Detection limits	MDL of 0.00084 ug/100cm ²	all measures	



Table E-3 Data Completeness Summary - Tent 3						
ANALYTE	Building/Area/ Unit	Sample Number Planned (Real & QC)	Sample Number Taken (Real & QC)	Project Decisions (Conclusions) & Uncertainty	Comments (RIN, Analytical Method, Qualifications, etc.)	
Beryllium	Tent 3 (interior and exterior)	38 samples (28 random/10 biased)	A39 samples (28 random/11 biased)	No contamination found at any location	IOCFR850; OSHA ID-125G RIN05Z1229: sample numbers 750-06062005-214-039 through numbers 750-06062005-214-077 ARefer to Attachment D, Beryllium Data Summary, Note 1, for discussion regarding random and bias samples. No results above the action-level (0.2 ug/100cm²) or investigative level (0.1 ug/100cm².)	
Radiological	Survey Area 5 Survey Class 3 Survey Unit: 750T02 Tent 3 (interior and exterior)	27 α TSA (17 random/10 biased) 27 α Smears (17 random/10 biased) 2 QC TSA 10% scan of the all interior and exterior surfaces	29 α TSA (17 random/12 biased) 29 α Smears (17 random/12 biased) 2 QC TSA 15% scan of the all interior and exterior surfaces	No contamination at any location; all values below unrestricted release levels	Transuranic DCGLs used.	
Radiological	Tent 3 Pad RSP-7.02 WRE Survey	14 α TSA 14 α Smears 2 m² scan at each TSA/RSA location, plus biased scanning on stains and at tent edges	14 α TSA 14 α Smears 2 m² scan at each TSA/RSA location, plus biased scanning on stains and at tent edges	No contamination at any location; all values below unrestricted release levels	Transuranic DCGLs used. Additional RSP 7.02 surveys of the asphalt pad areas outside the Tent structures will be performed, after tent demolition is complete, for waste disposal determinations (refer to RFCA Contact Record (DAP-035), dated 6/20/05).	

Korj.